

Technical Data

Jotun Anti-skid



Product description

Jotun Anti-Skid is aluminium oxide grains, intended to be spread into the last coat in a non-skid system. Available in extra coarse, coarse, medium and fine particle sizes.

Recommended use

For use on decks, floors, gangways and other areas where additional friction properties are required. The spreading is to take place in the wet film during application.

Recommended quantity

Fine particle size (180 - 250 µm) for coatings applied in 50 to 150 µm DFT, such as topcoats.
The recommended usage is 1,5 - 2,0 kg per 10 litres of paint

Medium particle size (400 - 600 µm) for coatings applied in 150 to 400 µm DFT, such as Jotamastic products and thick film topcoats.
The recommended usage is 2,5 - 3,3 kg per 10 litres of paint

Coarse particle size (700 - 1000 µm) for coatings applied in 400 to 1500 µm DFT, such as Baltoflake products.
The recommended usage is 3,0 - 4,0 kg per 10 litres of paint

Extra Coarse particle size (1200 - 1600 µm) for coatings applied in 400 to 1500 µm DFT, such as Baltoflake products.
The recommended usage is 3,5 - 4,0 kg per 10 litres of paint

If a more rough surface is required, the quantity may be increased.

Physical properties

Colour	Dark
Solids (vol %)*	100 ±
Flash point	N.A.

*Measured according to ISO 3233:1998 (E)

Hong Kong rules: Category of paints - Other vessel coatings; Exempt compound - N/A; Specific gravity: 3.92 kg/ltr (Coarse); 3.92 kg/ltr (Fine); 3.92 kg/ltr (Medium); 3.92 kg/ltr (Extra Coarse). Both VOC and Specific gravity values provided are typical values, subject to changes when different colour involved.

Surface preparation

Coated surfaces

According to specifications for the chosen topcoat.

Other surfaces

The coating may be used on other substrates. Please contact your local Jotun office for more information.

Storage

The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Handling

Handle with care.

Packing size

Jotun Anti-Skid extra coarse, coarse and medium in 25 kg in a bag
Jotun Anti-Skid Fine in 3 kg in a 3 litre container.

Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product can be used under conditions beyond our control, we can only guarantee the quality of the product itself. We also reserve the right to change the given data without notice. Minor product variations may be implemented in order to comply with local requirements.

If there is any inconsistency in the text the English (UK) version will prevail.

Jotun is a World Wide company with factories, sales offices and stocks in more than 50 countries. For your nearest local Jotun address please contact the nearest regional office or visit our website at www.jotun.com

ISSUED 26 NOVEMBER 2010 BY JOTUN
THIS DATA SHEET SUPERSEDES THOSE PREVIOUSLY ISSUED