



Conseal Touch-Up

Quick to apply. Fast to dry.

*High build. Single pack. Direct To Metal acrylic primer/finish.
Good impact resistance. Virtually unlimited colour choice.*



*When delivery time is short
When throughput depends
upon fast painting*

Conseal Touch-Up

Quick to apply. Fast to dry.

High build. Single pack. Direct To Metal acrylic primer/finish.

Good impact resistance. Virtually unlimited colour choice.

Product Properties

- Can be applied in a single coat up to 120 µm DFT - lower application costs and time saved
- Can be applied direct onto a clean steel surface - time saved and efficiency improved
- Surface dry in 20 minutes*, dry to recoat in 2 hours* keeping production on schedule, saving time, improving productivity
(* at 23°C)
- Good impact resistance with the flexibility to cope with steel expansion and contraction
- Excellent semi-gloss retention
- Suitable for application onto hand prepared surfaces (Minimum St 2 - ISO 8501-1:2007)
- Virtually unlimited colour choice with Jotun Multicolor tinting system

Technical Data

Solids (vol%)	49 ± 2	Thinner/Cleaner	No.7
Flash Point	25°C ± 2	VOC	440 gms/ltr UK-PG6/23(97). Appendix 3
Typical Film Thickness:			
Dry	120 µm	Colours	Available in most colours through Jotun Multicolor tinting system
Wet	245 µm		
Theo. Spreading Rate	4.1 m ² /ltr		



Jotun Paints (Europe) Ltd
Stather Road, Flixborough, DN15 8RR
Tel: (+44) 1724 400000
Fax: (+44) 1724 400100

Jotun (Ireland) Ltd
Unit K7 Marina Commercial Park,
Centre Park Road, Cork
Tel: (+353) 214 965955
Fax: (+353) 214 965992