



JOTUN

Ultra Topcoat

*The **ultra-fast-drying** high gloss finish*



*Surface dry in **20 minutes***

*For OEM
and all types
of machinery
and equipment
Virtually unlimited
choice of colours*

Ultra Topcoat

The **ultra-fast-drying** high gloss finish

Product Properties

- A quick drying glossy acrylic modified alkyd topcoat containing aromatic solvents
- Surface dry in just 20 minutes*, dry to recoat in 3 hours* keeping production on schedule, saving time and money (* at 23°C)
- High gloss and excellent colour retention properties
- Suitable for dry temperatures up to 120°C
- Virtually unlimited colour choice with Jotun Multicolor Industry tinting system (Colours made from Jotun Multicolor Industry base yellow are semi-gloss)
- For a quick drying system use with Pilot QD Primer (Surface dry in 15 minutes @ 23°C)

Technical Data

Solids (vol%)	46 ± 2	Thinner/Cleaner	No.7
	Black 37 ± 2	VOC	460 gms/ltr UK-PG6/23(97). Appendix 3
Flash Point	25°C ± 2		
Typical Film Thickness:		Colours	Available in most colours through Jotun Multicolor Industry tinting system
Dry	35 µm		
Wet	80 µm		
Theo. Spreading Rate	12.8 m ² /ltr		



Jotun Paints (Europe) Ltd
Stather Road, Flixborough, DN15 8RR
Tel: (+44) 1724 400000
Fax: (+44) 1724 400100

Jotun (Ireland) Ltd
Unit K7 Marina Commercial Park,
Centre Park Road, Cork
Tel: (+353) 214 965955
Fax: (+353) 214 965992